



1. SPRAYED POLYURETHANE INSULATION (TECH GUARD) W/TECH GUARD COATING SYSTEM
2. PREFABRICATED METAL CURB
3. OPTIONAL: WOOD NAILER
4. OPTIONAL: SHEET METAL RECEIVER AND REMOVABLE COUNTERFLASHING
5. SEALING MATERIAL—MUST BE CONTINUOUS FULL PERIMETER
6. 1" (25mm) MINIMUM BELOW TOP OF CURB
7. BASE OF UNIT EXTENDS 1/2" (13mm) MINIMUM BEYOND TOP OF CURB
8. MECHANICAL UNIT, HOOD, ETC.

- \* THE CURB, WOOD NAILER, AND SEAL STRIP ARE TO BE SUPPLIED BY THE CURB MANUFACTURER.
- \* ATTACH NAILER TO DECK WITH SUITABLE FASTENERS.
- \* WHEN POSSIBLE, THE MECHANICAL UNITS SHOULD NOT BE SET UNTIL THE ROOF SYSTEM HAS BEEN INSTALLED.



RAISED CURB DETAIL (dwg. 52)

3003 North 73rd Street, Scottsdale, AZ 85251  
402 East Grand Road, Tuscon, AZ 85705

DRAWN BY:

DATE:

APPROVED:

SCALE:

PROJECT NO:

DRAWING NO.