



1. IN CLIMATES WHERE THE WINTER TEMPERATURE REMAINS BELOW FREEZING FOR EXTENDED PERIODS OF TIME, NRCA SUGGESTS USING SPF-1 AND INTERIOR DRAINS OR THROUGH CURB SCUPPERS TO DRAIN THE ROOF.
2. THIS DETAIL SHOULD BE USED ONLY WHEN THE DECK IS SUPPORTED BY THE OUTSIDE WALL.
3. ATTACH NAILER TO WALL/DECK WITH SUITABLE FASTENERS.
4. FREQUENT NAILING OF SHEET METAL FLANGE IS NECESSARY TO MINIMIZE THERMAL MOVEMENT.
5. GUTTER BRACKETS ARE RECOMMENDED TO BE AT LEAST ONE GAUGE HEAVIER THAN GUTTER STOCK. DESIGN GUTTER EXPANSION JOINTS PLACED AT APPROPRIATE INTERVALS COMMENSURATE WITH TYPW OF METAL.
7. ELASTOMERIC SEALANT TO BE COMPATIBLE WITH COATING.



GUTTER (dwg. 38)

3003 NORTH 73RD STREET, SCOTTSDALE, AZ 85251
402 EAST GRAND ROAD, TUCSON, AZ 85705

DRAWN BY:	DRAWN BY:	APPROVED:
SCALE:	PROJECT NO:	DRAWING NO: