



1. SPRAYED POLYURETHANE INSULATION (TECH GUARD) W/TECH GUARD COATING SYSTEM
2. PREFABRICATED METAL CURB
3. OPTIONAL: WOOD NAILER
4. OPTIONAL: SHEET METAL RECEIVER AND REMOVABLE COUNTERPLASHING
5. SEALING MATERIAL-MUST BE CONTINUOUS FULL PERIMETER
6. 1" (25MM) MINIMUM BELOW TOP OF CURB
7. BASE OF UNIT EXTENDS 1/2" (13MM) MINIMUM BEYOND TOP OF CURB
8. MECHANICAL UNIT, HOOD, ETC.

- * THE CURB, WOOD NAILER, AND SEAL STRIP TO BE SUPPLIED BY THE CURB MANUFACTURER
- * ATTACH NAILER TO THE DECK WITH SUITABLE FASTENERS.
- * WHEN POSSIBLE, THE MECHANICAL UNITS SHOULD NOT BE SET UNTIL THE ROOF SYATEM HAS BEEN INSTALLED.



RAISED CURB DETAIL (dwg. 52)

3003 NORTH 73RD STREET, SCOTTSDALE, AZ 85251
402 EAST GRAND ROAD, TUCSON, AZ 85705

DRAWN BY:

DRAWN BY:

APPROVED:

SCALE:

PROJECT NO:

DRAWING NO: