



Modified Asphalt Primer Technical Data Sheet



Product Description:

Modified Asphalt Primer is an acrylic modified asphalt primer designed for use over various existing roofing substrates. This cost effective primer has outstanding adhesion characteristics.

Basic Use:

Modified Asphalt Primer can be used over smooth or granulated built-up, modified bitumen, metal, and single ply membranes as well as previously coated roofing substrates. Refer to Pro-Tech Products technical department for more information.

Packaging and Mixing:

Modified Asphalt Primer does not require thinning prior to use and is available in 5 gallon pails and 55 gallon drums. This product is available in black only. It is recommended to thoroughly mix all material prior to use utilizing an appropriate mixing blade.

Technical Data

Properties		Average Value
Viscosity		3000 CPS
Color		Black
Shelf Life		6 Months
Elongation		Approximately 800%
Adhesion		Excellent
Film Integrity		Excellent
Flash Point		N/A
Weight Per Gallon		9 LBS

Note: The above values are average values obtained from a laboratory and should serve only as a guide.

Modified Asphalt Primer Technical Data Sheet



Installation:

Modified Asphalt Primer can be spray applied using airless spray equipment, or a heavy nap roller or brushes for smaller areas. Spray application is the preferred method for application to achieve consistency and uniform film build. All surfaces shall be clean, dry and free of all dirt, grease, oil, and other surface contaminants that could interfere with proper adhesion to the roofing substrates.

Apply Modified Asphalt Primer at the maximum rate of ½-1.0 gallon per 100 sq. ft. per gallon over smooth non-porous or previously coated surfaces. Modified Asphalt Primer shall always be applied at temperatures of 50 degrees and rising and when weather conditions will permit drying before rain, dew or freezing temperatures occur.

Warranty:

No Specific warranties implied.

Technical Services:

Additional information, product brochures, and guide specifications are available. Customized application instructions are also available from our technical experts.

Pro-Tech Products, Inc.

3003 N. 73rd St.

Scottsdale AZ, 85251

Phone: (480) 945-7303

Fax: (480) 945- 8873

Website: [www. Pro-TechProducts.com](http://www.Pro-TechProducts.com)